Park Light Poles Embedded Style

DesignPole is manufactured with only the use of the highest quality concrete mixture that is centrifugally casted with pre-stressed spiral welded cages. Our specialized concrete mixture and patented polish exposes a unique surface that is distinctively sleek and smooth, which makes the poles naturally graffiti and tape resistant. Base mounted or embedded (direct burial) installations are available. Manufactured with the highest quality pre-stressed concrete and is available in a variety of standard and custom configurations.

Embedded Style

Embedded Styte													
	PRODUCT NUMBER	POLE HEIGHT	BASE O.D.	OVERALL LENGTH	EMBEDDED DEPTH	ULTIMATE GL. MOMENT	WEIGHT (LBS.)	MAXIMUM EPA/MPH(SQFT)*					
	Hombert	"A"	O.D.	"aL"	"B"	(FT. LBS.)	(2001)	80	90	100	110	120	130
	SLER-6.0	18'-10 3/8"	8 11/16"	23'-9 7/16"	4'-11"	40,400	1,040	11.5	9.9	8.6	7.6	6.8	6.1
	SLER-6.5	20'-6 1/16"	8 7/8"	25'-5 1/8"	4'-11"	41,830	1,130	12.7	10.9	9.5	8.4	7.5	6.7
	SLER-7.0	22'-1 3/4"	8 13/16"	27'-0 13/16"	4'-11"	40,970	1,190	13.6	11.6	10.1	9.0	8.0	7.2
	SLER-7.5	23'-9 7/16"	8 15/16"	28'-8 1/2"	4'-11"	42,120	1,270	14.7	12.6	11.0	9.7	8.7	7.8
	SLER-8.0	25'-5 1/8"	9 5/8"	30'-8 1/8"	5'-3"	48,550	1,460	16.5	14.1	12.3	10.9	9.7	8.8
	SLER-8.5	27'-0 13/16"	9 7/8"	32'-3 13/16"	5'-3"	50,140	1,550	17.7	15.2	13.3	11.7	10.5	9.4







